



# EasyCurve™ Mopping System

Curved foam mop for cleaning floors, walls, and ceilings

## Description

Designed especially for controlled environments, the EasyCurve mop consists of a flat, fabric-laminated mop head attached to a curved, stainless steel frame to provide superior performance and ease of use compared to other all-surface cleaning systems. The mop head securely attaches to the curved frame by a unique system of latching tabs, but remains simple and easy to remove.

All components are autoclavable, and sterile mop heads are available.

## Features and Benefits

- Very absorbent and drip-free
- Compatible with most common solutions/solvents
- Light weight and maneuverable
- Reduces operator fatigue
- Durable and simple, with no moving parts
- Ensures proper "lift and pull" technique

## Applicability

The information presented here is applicable to the part numbers shown below, as well as to any product containing the same materials and produced under the same conditions, regardless of product size or packaging configuration. Please contact a Contec sales representative for more details.

EZMP0100, EZMP0150 (sterile)

## Technical Data

Mop head component materials (cleaning surface first)	Knitted polyester fabric / hydrophilic urethane foam / .014" rigid polyester film
Construction	Multi-layer; flame bonded / inert, hi-temp adhesive
Dimensions; L x W x Thick., (cm)	35.8 x 11.0 x 2.0
Chemical compatibility	Recommended for use in most common disinfectant solutions, when made according to manufacturers' directions, for up to one hour. Not recommended for use in strong bleach solutions. Not compatible with acetone and other ketones.

Attribute; (units)	Value **	Test Method
Mop weight, dry; (g)	45	
Mop weight, wet (g)	298	
Sorbency in water		
Capacity; (mL/mop)	253	
Rate; (sec.)	1.3	
Non-volatile residue, NVR		IEST-RP-CC004.2, Sec. 6.1.2
In deionized water; (g/mop)	.021	
In isopropanol; (g/mop)	.063	
Ionics		
Sodium; (ppm)	ND	
Chloride; (ppm)	ND	
Silicon; (ppm)	ND	
Particles ≥ 0.5µm; (x10 <sup>6</sup> /mop)	2.2	IEST-RP-CC004.2, Sec. 5.2
Fibers > 100µm; (x10 <sup>3</sup> /mop)	1.2	IEST-RP-CC004.2, Sec. 5.2

Notes:

\*\* ND = None detected; levels are below detection limit of test equipment

- 1) Data shown are typical values and should not be used as product specifications.
- 2) Valid product comparisons may only be obtained through side-by-side testing in the same test facility, under similar conditions.
- 3) Current and/or comparison data may be available. Please contact a Contec sales representative for details.

Revision date: 12/11/07



P.O. Box 530  
Spartanburg, SC 29304 USA  
Phone: +1-864-503-8333  
Fax: +1-864-503-8444  
Toll free US, Canada, PR: 1-800-289-5762

**Customer Service**  
United States: 1-866-855-4682  
Europe/Asia: +1-864-699-8257  
e-mail: wipers@contecinc.com  
www.contecinc.com