



PROSAT[®] Wipe, Quiltec[®] I

Quiltec polyester wipes with 100% IPA

Description

The Quiltec wipes are made using two layers of knitted polyester fabric that have been bonded together to form a stronger wipe with greater solvent holding and delivery capacity. The wipe features sealed edges resulting in the cleanest wipe possible for the most demanding applications.

Features and Benefits

- Increased strength, durability and solution capacity
- Laser-cut edges seals fibers at the wipes edge
- Extremely low in particle and fiber contamination
- Very abrasion and chemical resistant

Applicability

The information presented here is applicable to the part numbers shown below, as well as to any product containing the same materials and produced under the same conditions, regardless of product size or packaging configuration. Please contact a Contec sales representative for more details.

PSQT0014, PSQT0019, PSQT0026, PSQT0031

Technical Data

Wipe material	100% knitted polyester	
Wipe construction	2-layer, ultrasonically bonded	
Solution of saturation; (blend ratio and constituents)	100% isopropanol	
Attribute, wipe; (units)	Value **	Test Method
Basis weight; (g/m ²)	240	
Non-volatile residue, NVR		IEST-RP-CC004.2, Sec. 6.1.2
In deionized water; (g/m ²)	N/A	
In isopropanol; (g/m ²)	N/A	
Specific ions		IEST-RP-CC004.2, Sec. 6.2.2
Sodium; (ppm)	0.696	
Chloride; (ppm)	1.145	
Silicone; (ppm)	ND	
Particles, readily releasable		IEST-RP-CC004.2, Sec. 5.1
P ≥ 0.3µm; (x10 ⁶ /m ²)	N/A	
P ≥ 0.5µm; (x10 ⁶ /m ²)	6.5	
Fibers > 100µm; (x10 ³ /m ²)	0.74	IEST-RP-CC004.2, Sec. 5.2
Saturation volume tolerance;		N/A
< 300 mL	+/- 12%	
300 -1666 mL	+/- 3%	
> 1666 mL	+/- 50 mL	

** ND = None detected; levels are below detection limit of test equipment

Notes:

- 1) Data shown are typical values and should not be used as product specifications.
- 2) Valid product comparisons may only be obtained through side-by-side testing in the same test facility, under similar conditions.
- 3) Current and/or comparison data may be available. Please contact a Contec sales representative for details.

Revision date: 02/04/10



P.O. Box 530
Spartanburg, SC 29304 USA
Phone: +1-864-503-8333
Fax: +1-864-503-8444
Toll free US, Canada, PR: 1-800-289-5762

Customer Service
United States: 1-866-855-4682
Europe/Asia: +1-864-699-8257
e-mail: wipers@contecinc.com
www.contecinc.com