

SAFETY DATA SHEET

1. Identification

| Product identifier | Presaturated wipes containing 75% Isoprop (FLIQ) (No IATA) | oyl Alcohol, 25% Propylene Glycol Methyl Ether | |
|---------------------------------|--|---|--|
| Other means of identification | | | |
| SDS number | FLIQ3029 | | |
| Product code | PSQT0015 | | |
| Recommended use | Saturated cleaning wipes. | | |
| Recommended restrictions | Industrial use only. | | |
| Manufacturer/Importer/Supplier/ | Distributor information | | |
| Company Name | Contec, Inc. | | |
| Address | 525 Locust Grove | | |
| | Spartanburg, SC 29303 | | |
| | USA | | |
| Telephone | 1-864-503-8333 | | |
| Email | SDS@contecinc.com | | |
| Emergency phone number | Call CHEMTREC day or night | | |
| | USA/Canada: 1.800.424.9300 | | |
| | Mexico: 1.800.681.9531 | | |
| | Outside USA/Canada: +1.703.527.3887 | | |
| 2. Hazard(s) identification | | | |
| Physical hazards | Flammable liquids | Category 2 | |
| Health hazards | Serious eye damage/eye irritation | Category 2 | |
| | Specific target organ toxicity, single exposure | Category 3 narcotic effects | |
| OSHA defined hazards | Not classified. | | |
| Label elements | | | |
| | | | |
| Signal word | Danger | | |
| Hazard statement | Highly flammable liquid and vapor. Causes se dizziness. | rious eye irritation. May cause drowsiness or | |
| Precautionary statement | | | |
| Prevention | Keep away from heat/sparks/open flames/hot surfaces No smoking. Keep container tightly closed. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist/vapors. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. | | |
| Response | If in eyes: Rinse cautiously with water for seve easy to do. Continue rinsing. If eye irritation pe | ntaminated clothing. Rinse skin with water/shower. ral minutes. Remove contact lenses, if present and ersists: Get medical advice/attention. If inhaled: able for breathing. Call a poison center/doctor if you edia to extinguish. | |
| 04.0.00 | Otava in a well ventilated along. Keen contains | which the alassa I Kasa asal | |

Store in a well-ventilated place. Keep container tightly closed. Keep cool.

DisposalDispose of contents/container in accordance with local/regional/national/international regulations.Hazard(s) not otherwiseNone known.

Hazard(s) not otherwis classified (HNOC)

Storage

Although the product as a whole is in solid format, the product does not meet the OSHA HCS definition of a flammable solid as per Appendix B to 1910.1200 - Physical Hazard Criteria, section B.7.1 and B. 7.2.

3. Composition/information on ingredients

Mixtures

| Mixtures | | |
|--|--|--|
| Chemical name | CAS number | % |
| Propan-2-ol | 67-63-0 | 75 |
| 1-Methoxy-2-propanol | 107-98-2 | 25 |
| Composition comments | All concentrations are in percent by volume. | |
| 4. First-aid measures | | |
| Inhalation | If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a doctor/physician if you feel unwell. | poison center or |
| Skin contact | Rinse skin with water/shower. Get medical attention if irritation develops and pers | ists. |
| Eye contact | Immediately flush eyes with plenty of water for at least 15 minutes. Remove conta present and easy to do. Continue rinsing. Get medical attention if irritation develop | |
| Ingestion | Not relevant, due to the form of the product. However: In case of ingestion: Rinse medical attention if symptoms occur. | mouth. Get |
| Most important symptoms/effects, acute and delayed | Direct contact with eyes causes serious eye irritation. Symptoms may include stin redness, swelling, and blurred vision. In high concentrations, vapors are narcotic a headache, fatigue, dizziness and nausea. | |
| Indication of immediate medical attention and special treatment needed | Provide general supportive measures and treat symptomatically. Thermal burns: F immediately. While flushing, remove clothes which do not adhere to affected area ambulance. Continue flushing during transport to hospital. Keep victim under obse Symptoms may be delayed. | . Call an |
| General information | Ensure that medical personnel are aware of the material(s) involved, and take pre protect themselves. | cautions to |
| 5. Fire-fighting measures | | |
| Suitable extinguishing media | Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2). | |
| Unsuitable extinguishing media | Do not use water jet as an extinguisher, as this will spread the fire. | |
| Specific hazards arising from the chemical | May burn with invisible flame. Vapors may form explosive mixtures with air. Vapor than air and may spread near ground to sources of ignition. Vapors may travel condistance to a source of ignition and flash back. During fire, gases hazardous to he formed. Carbon oxides. Organic compounds. | nsiderable |
| Special protective equipment and precautions for firefighters | Self-contained breathing apparatus and full protective clothing must be worn in ca | se of fire. |
| Fire fighting equipment/instructions | In case of fire and/or explosion do not breathe fumes. Cool containers exposed to water. Move containers from fire area if you can do so without risk. | flames with |
| Specific methods | Use standard firefighting procedures and consider the hazards of other involved n | naterials. |
| General fire hazards | Solid containing flammable liquid. | |
| 6. Accidental release meas | sures | |
| Personal precautions, protective equipment and emergency procedures | Keep unnecessary personnel away. Keep people away from and upwind of spill/le ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear a protective equipment and clothing during clean-up. Avoid breathing mist/vapors. A skin, eyes and clothing. Do not touch damaged containers or spilled material unle appropriate protective clothing. Ventilate closed spaces before entering them. Loo should be advised if significant spillages cannot be contained. For personal protect 8 of the SDS. | appropriate Avoid contact wi ss wearing cal authorities |
| Methods and materials for containment and cleaning up | Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate a combustibles (wood, paper, oil, etc.) away from spilled material. Avoid release to the liquid solvent solution is miscible in water. Spills are very unlikely, because the has absorbed the liquid solvent solution. In the event of a spill, contain with an ine Collect the wipes with a non sparking tool and absorb or wipe any residual liquids suitable container. | the environment e wiper fabric ert absorbent. |
| | Never return spills to original containers for re-use. For waste disposal, see sectio | n 13 of the SD |
| | | |

Environmental precautions Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

| Precautions for safe handling | WARNING! Used wipes may catch fire if improperly discarded or stored near ignition sources. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Avoid breathing mist/vapors. Avoid contact with skin, eyes and clothing. Avoid prolonged exposure. Wash thoroughly after handling. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. Take precautionary measures against static discharges. |
|--|---|
| Conditions for safe storage, including any incompatibilities | Keep away from heat, sparks and open flame. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Keep containers closed when not in use. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS). |

8. Exposure controls/personal protection

Occupational exposure limits

| Components | Туре | Value | |
|---|-------------------------------------|---|--|
| Propan-2-ol (CAS 67-63-0) | PEL | 980 mg/m3 | |
| | | 400 ppm | |
| US. ACGIH Threshold Limit Values | ; (TLV) | | |
| Components | Туре | Value | |
| 1-Methoxy-2-propanol (CAS 107-98-2) | STEL | 100 ppm | |
| | TWA | 50 ppm | |
| Propan-2-ol (CAS 67-63-0) | STEL | 400 ppm | |
| | TWA | 200 ppm | |
| NIOSH. Immediately Dangerous to | Life or Health (IDLH) Values | as amended | |
| Components | Туре | Value | |
| | | | |
| Propan-2-ol (CAS 67-63-0) | IDLH | 2 % | |
| Propan-2-ol (CAS 67-63-0) | IDLH | 2 % 2000 ppm | |
| US. NIOSH: Pocket Guide to Chem | | 2000 ppm | |
| | | | |
| US. NIOSH: Pocket Guide to Chem | ical Hazards | 2000 ppm | |
| US. NIOSH: Pocket Guide to Chem Components 1-Methoxy-2-propanol (CAS | ical Hazards Type | 2000 ppm Value | |
| US. NIOSH: Pocket Guide to Chem Components 1-Methoxy-2-propanol (CAS | ical Hazards Type | 2000 ppm Value 540 mg/m3 | |
| US. NIOSH: Pocket Guide to Chem Components 1-Methoxy-2-propanol (CAS | ical Hazards Type STEL | 2000 ppm Value 540 mg/m3 150 ppm | |
| US. NIOSH: Pocket Guide to Chem Components 1-Methoxy-2-propanol (CAS | ical Hazards Type STEL | 2000 ppm Value 540 mg/m3 150 ppm 360 mg/m3 | |
| US. NIOSH: Pocket Guide to Chem Components 1-Methoxy-2-propanol (CAS 107-98-2) | ical Hazards Type STEL TWA | 2000 ppm Value 540 mg/m3 150 ppm 360 mg/m3 100 ppm | |
| US. NIOSH: Pocket Guide to Chem Components 1-Methoxy-2-propanol (CAS 107-98-2) | ical Hazards Type STEL TWA | 2000 ppm Value 540 mg/m3 150 ppm 360 mg/m3 100 ppm 1225 mg/m3 | |

| ACGIH Biological Exposu | re Indices (BEI) | | | | |
|---------------------------|------------------|-------------|----------|---------------|--|
| Components | Value | Determinant | Specimen | Sampling Time | |
| Propan-2-ol (CAS 67-63-0) | 40 mg/l | Acetone | Urine | * | |

* - For sampling details, please see the source document.

Exposure guidelines Follow standard monitoring procedures.

US - California OELs: Skin designation

1-Methoxy-2-propanol (CAS 107-98-2) Can be absorbed through the skin.

| Appropriate engineering | Good general ventilation should be used. Ventilation rates should be matched to conditions. If |
|-------------------------|---|
| controls | applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. |

Individual protection measures, such as personal protective equipment

Eye/face protection If splashing is possible, wear safety glasses with side shields (or goggles).

| Skin protection | |
|-----------------------------------|--|
| Hand protection | Wear appropriate chemical resistant gloves. Take note of the information given by the manufacturer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). Recommended materials: Neoprene. Polyvinyl chloride (PVC). Polyethylene. Chlorinated polyethylene (or Chlorosulfonated polyethylene). Natural rubber. Nitrile rubber/Nitrile latex - NBR. Ethyl vinyl alcohol laminate ("EVAL"). Unsuitable materials: Polyvinyl alcohol (PVA). |
| Skin protection | |
| Other | Wear suitable protective clothing. |
| Respiratory protection | If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Chemical respirator with organic vapor cartridge and full facepiece. Wear NIOSH approved respirator appropriate for airborne exposure at the point of use. Check with respiratory protective equipment suppliers. |
| Thermal hazards | Wear appropriate thermal protective clothing, when necessary. |
| General hygiene considerations | When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. |

9. Physical and chemical properties

| Appearance | |
|--|--|
| Physical state | Solid. |
| Form | Wipes saturated with liquid. |
| Color | Colorless. |
| Odor | Alcohol-like. |
| Odor threshold | Property has not been measured. |
| рН | Property has not been measured. (liquid) |
| Melting point/freezing point | Property has not been measured. (liquid) |
| Initial boiling point and boiling range | 179.6 - 242.6 °F (82 - 117 °C) (liquid) |
| Flash point | 59 °F (15 °C) Tag Closed Cup ASTM D56 (liquid) |
| Evaporation rate | 2.3 (n-Butyl Acetate = 1) (liquid) |
| Flammability (solid, gas) | Wipes will burn if involved in a fire. |
| Upper/lower flammability or exp | losive limits |
| Explosive limit - lower (%) | 2 % (liquid) |
| Explosive limit - upper (%) | 12 % (liquid) |
| Vapor pressure | 27 mm Hg (68 °F (20 °C) (liquid)) |
| Vapor density | 2.3 Air = 1 (liquid) |
| Relative density | 0.82 (68 °F (20 °C) (liquid)) |
| Solubility(ies) | |
| Solubility (water) | Soluble in water. (liquid) |
| Partition coefficient (n-octanol/water) | Not applicable to mixtures. |
| Auto-ignition temperature | Property has not been measured. |
| Decomposition temperature | Property has not been measured. |
| Viscosity | Property has not been measured. (liquid) |
| Other information | |
| Explosive properties | Not explosive. |
| Kinematic viscosity | Property has not been measured. (liquid) |
| Oxidizing properties | Not oxidizing. |
| Percent volatile | 100 % (IPA) |
| | |

10. Stability and reactivity

Reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport.

| Chemical stability | Material is stable under normal conditions. |
|---------------------------------------|--|
| Possibility of hazardous reactions | No dangerous reaction known under conditions of normal use. |
| Conditions to avoid | Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials. |
| Incompatible materials | Aldehydes. Halogenated organics. Halogens. Strong acids. Strong oxidizing agents. |
| Hazardous decomposition products | Combustion may produce: Oxides of carbon and other organic substances. |

11. Toxicological information

Information on likely routes of exposure

| Inhalation | May cause drowsiness or dizziness. Headache. Nausea, vomiting. Prolonged inhalation of vapors may be harmful. |
|--|---|
| Skin contact | Prolonged skin contact may cause temporary irritation. |
| Eye contact | Direct contact: Causes serious eye irritation. |
| Ingestion | Not relevant, due to the form of the product. |
| Symptoms related to the physical, chemical and toxicological characteristics | Direct contact with eyes causes serious eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. In high concentrations, vapors are narcotic and may cause headache, fatigue, dizziness and nausea. |

Information on toxicological effects

Acute toxicity

Not relevant, due to the form of the product in its manufactured and shipped state.

| Components | Species | Test Results |
|--------------------------------------|---|--|
| 1-Methoxy-2-propanol (CAS 107- | 98-2) | |
| Acute | | |
| Dermal | | |
| LD50 | Rabbit | 13000 mg/kg |
| Oral | | |
| LD50 | Rat | > 5000 mg/kg |
| Propan-2-ol (CAS 67-63-0) | | |
| Acute | | |
| Dermal | | |
| LD50 | Rabbit | 12870 mg/kg |
| Inhalation | | |
| Vapor | | |
| LC50 | Rat | 72.6 mg/l, 4 hours |
| Oral | | |
| LD50 | Rat | 4710 mg/kg |
| Skin corrosion/irritation | Prolonged skin contact may cause temporary irritat | ion. |
| Serious eye damage/eye irritation | Direct contact: Causes serious eye irritation. | |
| Respiratory or skin sensitizatio | n | |
| Respiratory sensitization | Not a respiratory sensitizer. | |
| Skin sensitization | This product is not expected to cause skin sensitization | ation. |
| Germ cell mutagenicity | No data available to indicate product or any compo mutagenic or genotoxic. | nents present at greater than 0.1% are |
| Carcinogenicity | Not classifiable as to carcinogenicity to humans. | |
| IARC Monographs. Overall | Evaluation of Carcinogenicity | |
| Not listed. | | |
| NTP Report on Carcinogen | S | |
| Not listed. | | |
| | ed Substances (29 CFR 1910.1001-1053) | |
| Not listed. | - | |
| Reproductive toxicity | This product is not expected to cause reproductive | or developmental effects. |

| Specific target organ toxicity - single exposure | In high concentrations, vapors are narcotic and may cause headache, fatigue, dizziness and nausea. |
|--|--|
| Specific target organ toxicity - repeated exposure | Not classified. |
| Aspiration hazard | Not an aspiration hazard. |
| Chronic effects | Frequent or prolonged contact may defat and dry the skin. |

12. Ecological information

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

| Components | | Species | Test Results | | | |
|--|--|--|--|--|--|--|
| Propan-2-ol (CAS 67-63-0) | | | | | | |
| Aquatic | | | | | | |
| Acute | | | | | | |
| Crustacea | LC50 | Daphnia magna | > 10000 mg/l, 24 hours | | | |
| Fish | LC50 | Pimephales promelas | 9640 mg/l, 96 hours | | | |
| Chronic | | | | | | |
| Crustacea | EC50 | Daphnia magna | > 100 mg/l, 21 days | | | |
| | NOEC | Daphnia magna | 141 mg/l, 16 days | | | |
| | | | 30 mg/l, 21 days | | | |
| sistence and degradability | No data is | available on the degradability of any | ingredients in the mixture. | | | |
| accumulative potential | Bioconcentration potential is low. | | | | | |
| Partition coefficient n-octa 1-Methoxy-2-propanol (CAS Propan-2-ol (CAS 67-63-0) | • | og Kow) -0.49 0.05 | | | | |
| bility in soil | Isopropyl | Isopropyl alcohol is highly mobile in soil. | | | | |
| ner adverse effects | The product contains a volatile organic compound which has a photochemical ozone creation potential. | | | | | |
| . Disposal consideratio | ons | | | | | |
| posal instructions | accordance | | ers at licensed waste disposal site. Dispose in I wipes must be disposed in a closed container. | | | |
| cal disposal regulations | Dispose ir | Dispose in accordance with all applicable regulations. | | | | |
| zardous waste code | D001: Waste Flammable material with a flash point <140 F | | | | | |

| | | te code sł company. | assigi | ned in | discussi | on betw | een the us | er, the pro | oducer and the was | te |
|--|---|------------------------|--------|--------|----------|---------|------------|-------------|--------------------|----|
| | - | <i>.</i> . | | | | | | | | |

| Waste from residues / unused products | Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner. |
|--|---|
| Contaminated packaging | Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers. |

14. Transport information

DOT

| UN1993 |
|---|
| Flammable liquids, n.o.s. (Isopropanol, Propylene Glycol Methyl Ether) |
| |
| 3 |
| - |
| 3 |
| II |
| |
| No. |
| • Read safety instructions, SDS and emergency procedures before handling. |
| IB2, T7, TP1, TP8, TP28 |
| 150 |
| 202 |
| |

| Packaging bulk | 242 | |
|--|---|--|
| ΙΑΤΑ | | |
| UN number | - | |
| UN proper shipping name | IATA: Not permitted for | transport. |
| Transport hazard class(es) | | |
| Class | - | |
| Subsidiary hazard | - | |
| Packing group | - | |
| Environmental hazards | No. | |
| | IATA classification is no | t relevant as the material is not transported by air. |
| IMDG | | |
| UN number | UN1993 | |
| UN proper shipping name | FLAMMABLE LIQUID, I | N.O.S. (Isopropanol, Propylene Glycol Methyl Ether) |
| Transport hazard class(es) | | |
| Class | 3 | |
| Subsidiary hazard | - | |
| Packing group | II | |
| Environmental hazards | | |
| Marine pollutant | No. | |
| EmS | F-E, <u>S-E</u> | SDC and amorganou presedures before bondling |
| | Not established. | , SDS and emergency procedures before handling. |
| Transport in bulk according to Annex II of MARPOL 73/78 and | NUL ESTADIISTIEU. | |
| the IBC Code | | |
| | | |
| 15. Regulatory information | | |
| US federal regulations | This product is a "Hazar Standard, 29 CFR 1910 | dous Chemical" as defined by the OSHA Hazard Communication .1200. |
| TSCA Section 12(b) Exp | ort Notification (40 CFR | 707, Subpt. D) |
| Not regulated. | | |
| CERCLA Hazardous Sub | ostance List (40 CFR 30 | 2.4) |
| Propan-2-ol (CAS 67- | 63-0) | Listed. |
| SARA 304 Emergency re | lease notification | |
| Not regulated. | | |
| OSHA Specifically Regu | lated Substances (29 C | FR 1910.1001-1053) |
| Not listed. | | |
| Toxic Substances Control A | · · · · | All components of the mixture on the TSCA 8(b) inventory are designated 'active". |
| Superfund Amendments and Rea | authorization Act of 198 | 6 (SARA) |
| SARA 302 Extremely hazard | ous substance | |
| Not listed. | | |
| SARA 311/312 Hazardous chemical | Yes | |
| Classified hazard categories | Flammable (gases, aero Serious eye damage or Specific target organ to | |

Specific target organ toxicity (single or repeated exposure)

SARA 313 (TRI reporting)

| Chemical name | CAS number | % by wt. | |
|---------------------------|------------|----------|--|
| Propan-2-ol | 67-63-0 | 75 | |
|)ther federal regulations | | | |

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130) Not regulated.

Safe Drinking Water Act Not regulated. (SDWA)

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

Propan-2-ol (CAS 67-63-0)

Low priority

US state regulations

US. Massachusetts RTK - Substance List

1-Methoxy-2-propanol (CAS 107-98-2) Propan-2-ol (CAS 67-63-0)

US. New Jersey Worker and Community Right-to-Know Act

1-Methoxy-2-propanol (CAS 107-98-2) Propan-2-ol (CAS 67-63-0)

US. Pennsylvania Worker and Community Right-to-Know Law

1-Methoxy-2-propanol (CAS 107-98-2) Propan-2-ol (CAS 67-63-0)

US. Rhode Island RTK

1-Methoxy-2-propanol (CAS 107-98-2) Propan-2-ol (CAS 67-63-0)

California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

International Inventories

| Country(s) or region | Inventory name | On inventory (yes/no)* |
|-----------------------------|---|------------------------|
| Australia | Australian Inventory of Industrial Chemicals (AICIS) | Yes |
| Canada | Domestic Substances List (DSL) | Yes |
| Canada | Non-Domestic Substances List (NDSL) | No |
| China | Inventory of Existing Chemical Substances in China (IECSC) | Yes |
| Europe | European Inventory of Existing Commercial Chemical Substances (EINECS) | Yes |
| Europe | European List of Notified Chemical Substances (ELINCS) | No |
| Japan | Inventory of Existing and New Chemical Substances (ENCS) | Yes |
| Korea | Existing Chemicals List (ECL) | Yes |
| New Zealand | New Zealand Inventory | Yes |
| Philippines | Philippine Inventory of Chemicals and Chemical Substances (PICCS) | Yes |
| Taiwan | Taiwan Chemical Substance Inventory (TCSI) | Yes |
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory | Yes |

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

| Issue date | 14-June-2024 |
|---------------------|--|
| Revision date | 19-June-2025 |
| Version # | 01a |
| Further information | HMIS Rating: X - Ask Supervisor |
| HMIS® ratings | Health: 2 Flammability: 3 Physical hazard: 0 Personal protection: X |

| List of abbreviations | DOT: Department of Transportation. EC50: Effective Concentration, 50%. IATA: International Air Transport Association. IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk. IDLH: Immediately Dangerous To Life or Health. IMDG: International Maritime Dangerous Goods. LC50: Lethal Concentration, 50%. LD50: Lethal Dose, 50%. MARPOL: International Convention for the Prevention of Pollution from Ships. NOEC: No Observed Effect Concentration. PEL: Permissible Exposure Limit. STEL: Short-Term Exposure Limit. |
|-----------------------|--|
| | TWA: Time Weighted Average Value. |
| Disclaimer | Contec, Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available. |