## Sterile Polynit Heatseal Wipes

## 100% no-run interlock knit polyester wipes with sealed edges

Sterile Polynit Heatseal Wipes are made of 100% knitted polyester that is laser cut to bond the fibers at the edges of the wipe. This creates a very clean nonabrasive edge that allows full utilization of the wipe surface. The wipe is chemical resistant and exceptionally low in particles and extractable residue making it ideal for critical cleaning. They have good sorbency with solvents and are abrasion and chemical resistant.

These wipes are validated sterile to a 10<sup>-6</sup> SAL per ANSI/AAMI/ISO 11137 guidelines so it can be used in the highest grade life science cleanrooms.



Features	Benefits
Laundered knitted 100% polyester fabric	<ul><li>Extremely low levels of particles and fibers</li><li>Good abrasion and chemical resistance</li></ul>
Laser-cut sealed edges	<ul><li>Prevents release of fibers</li><li>Clean nonabrasive edges allow for full utilization of the wipes surface</li></ul>
Validated sterile to a 10 <sup>-6</sup> SAL per ANSI/ AAMI/ISO 11137	• Suitable for use in ISO 3-8 (Grade A/B) cleanrooms

Part No.	Description		Size	Packaging
PN-99IR	Sterile Polynit Heatseal Wipes, Flat stacked	Sterile	9" x 9" (230 x 230 mm)	10/bag; 100 bags/case
LWPS0006	Sterile Polynit Heatseal Wipes, Flat stacked	Sterile	9" x 9" (230 x 230 mm)	25/bag; 48 bags/case
LWPS0007	Sterile Polynit Heatseal Wipes, Flat stacked	Sterile	12" x 12" (305 x 305 mm)	25/bag; 40 bags/case
LWPS0027	Sterile Polynit Heatseal Wipes, Flat stacked	Sterile	9" x 9" (230 x 230 mm)	75/bag; 16 bags/case

PDSW017 | 092122 | Ref: 9502

Copyright © 2022 Contec, Inc. All rights reserved.

Contact us: info@contecinc.com contecinc.com Contec, Inc. Spartanburg, SC 29303 USA tel: +1-864-503-8333



Product Infor	mation							
Material	•	• 100% polyester						
Construction	•	Interlock Knit, no-run						
Packaging mate	erials •	<ul> <li>Outer bags (OB1, OB2), low density polyethylene (LDPE) Case (CS), corrugated fiberboard (PAP)</li> </ul>						
Environment	•	• ISO 3-8 Grade A/B						
Shelf life	•	• 2 years from manufacturing date						
Technical Dat	a							
Attribute (units)		Тур	oical Value	Test Method				
Basis weight, nominal; (g/m²)			140	Contec Method				
Sorbent capacity; (mL/m²)			327	IEST-RP-CC004.3, Sec. 8.1				
Sorptive rate; (seconds)			<1	IEST-RP-CC0	04.3, Sec. 8.2			
Non-volatile residue, NVR				IEST-RP-CC0	04.3, Sec. 7.1.2			
In deionized water; (g/m²)		(g/m²)		0.011				
In isopropyl alcohol; (g/m²)		(g/m²)		0.005				
Specific ions					IEST-RP-CC0	04.3, Sec. 7.2.2		
	Sodium;	(ppm)	0.057					
Chloride; (ppm)			0.015					
Particles, readi	ly releasable							
Particles <u>&gt;</u> 0.5µm; (x10 <sup>6</sup> /m <sup>2</sup> )			2.2		IEST-RP-CC004.2, Sec. 5.1			
Fibers ≥ 100µm; (x 10³/m²)		0.122		IEST-RP-CC004.2, Sec. 5.2				
Packaging	EA/OB1	OB1/	OB2	OB2/CS	EA/CS			
LWPS0006	25	4		12	1,200			
LWPS0007	25	4		10	1,000			
PN-99IR	10	10	0	10	1,000			
	EA/OB1	OB1/	OB2	OB2/OB3	OB3/CS	EA/CS		
LWPS0027	75	1		2	8	1,200		

## **Recycle Symbols**



EA = each; OB = outer bag; CS = case

Notes

a) The data shown are typical values and should not be used as product specifications.

b) Valid product comparisons may only be obtained through side-by-side testing in the same test facility, under similar conditions.

c) Current and/or comparison data may be available. Please contact a Contec sales representative for details.

## Test Methods

1. CTM = Contec Test Method

2. IEST-RP-CC004.3 = Evaluating Wiping Materials Used in Cleanroom and Other Controlled Environments, Institute of environmental Sciences and Technology, Rolling Meadows IL.

PDSW017 | 092122 | Ref: 9502

Copyright  $\ensuremath{\mathbb{C}}$  2022 Contec, Inc. All rights reserved.

Contact us: info@contecinc.com contecinc.com Contec, Inc. Spartanburg, SC 29303 USA tel: +1-864-503-8333

