

# PROSAT® PS-SI Delta™ Wipes

## 100% nonwoven polyester wipes

PROSAT® PS-SI Delta™ Wipes feature 100% nonwoven polyester presaturated with a blend of 10% isopropyl alcohol and 90% DI water. Designed for the semiconductor industry, the PROSAT PS-SI Delta Wipes provides the cleanest nonwoven wipe available. The durable wipe is made from 100% nonwoven polyester fibers, hydroentangled into an extremely soft, clean, and strong fabric which is very low in both particles and extractables.

The solution blend of 10% IPA and 90% deionized water combines cleaning effectiveness with safety. The semiconductor grade solution is 0.2 micron filtered and meets SEMI specifications for metals. This product has a low IPA concentration for increased safety in semiconductor facilities.



Available in convenient, easy to use peel and reseal pouches which are individually lot numbered for traceability. These specially designed pouches preserve cleanliness and solvent saturation levels. PROSAT presaturated wipes are an effective efficient and convenient method of cleaning process tools and other equipment.



Features	Benefits
Durable nonwoven polyester	• Low in both particles and extractables
Resealable pouch	• Convenient and easy to use
Semiconductor grade solution	• 0.2 micron filtered and meets SEMI requirements for metals
Presaturated wipes	• Provide increased process control while reducing VOCs and amount of solvent used

Part No.	Description	Size	Packaging
PS-SI	PROSAT PS-SI Delta Wipes, Presaturated with 10% IPA and 90% DI Water	9" x 9" (230 x 230 mm)	30/pouch; 50 pouches/case

## Product Information

Material	• 100% polyester
Construction	• Hydroentangled nonwoven
Packaging materials	• Outer bags (OB1), low density polyethylene (LDPE)  Case (CS), corrugated fiberboard (PAP) 
Environment	• ISO 5-8    Grade C/D



## Technical Data

Attribute (units)	Typical Value	Test Method
Basis weight, nominal; (g/m <sup>2</sup> )	69	Contec Method
Non-volatile residue, NVR		IENT-RP-CC004.3, Sec. 7.1.2
In deionized water; (g/m <sup>2</sup> )	0.055	
In isopropyl alcohol; (g/m <sup>2</sup> )	0.008	
Specific ions		IENT-RP-CC004.3, Sec. 7.2.2
Sodium; (ppm)	1.9	
Chloride; (ppm)	4.7	
Particles, readily releasable		IENT-RP-CC004.2, Sec. 5.1
Particles ≥ 0.5µm; (x10 <sup>6</sup> /m <sup>2</sup> )	16.5	
Fibers ≥ 100µm; (x 10 <sup>3</sup> /m <sup>2</sup> )	1.0	

## Recycle Symbols

PET	
HDPE	
LDPE	
PP	
PAP	

Packaging	EA/PCH	PCH/OB1	OB1/CS	EA/CS
PS-SI	30	10	5	1,500

EA = each; OB = outer bag; PCH = pouch; CS = case; LBS = pounds

VOC Content	VOC (LBS/CS)	VOC (LBS/PCH)
PS-SI	4.73	0.09

## Notes

- a) The data shown are typical values and should not be used as product specifications.  
b) Valid product comparisons may only be obtained through side-by-side testing in the same test facility, under similar conditions.  
c) Current and/or comparison data may be available. Please contact a Contec sales representative for details.  
d) All of Contec's packaging is compatible with hydrogen peroxide gassing applications.  
e) These wipes are free of lint and loose fibers, and meet the definition of lint-free/low linting wipes according to the United States Pharmacopoeia Chapter 797 (USP-NF General Chapter <797> Pharmaceutical Compounding -Sterile Preparations) and the Institute of Environmental Sciences and Technology Recommended Practice IEST-RP-CC004.4

## Test Methods:

- CTM = Contec Test Method
- IENT-RP-CC004.3 = Evaluating Wiping Materials Used in Cleanroom and Other Controlled Environments, Institute of environmental Sciences and Technology, Rolling Meadows IL.

PDSW038 | 090822

Copyright © 2022 Contec, Inc. All rights reserved.

Contact us:  
[info@contecinc.com](mailto:info@contecinc.com)  
[contecinc.com](http://contecinc.com)

Contec, Inc.  
Spartanburg, SC 29303 USA  
tel: +1-864-503-8333

