Quiltec[®] I Wipes

2-ply quilted polyester wipes with sealed edges

Quiltec[®] I Wipes offer the highest sorptive capacity of any sealed edge wipe available. It is manufactured using two layers of knitted polyester fabric that are laminated together to form a stronger, more adsorbent wipe. Additional fluid is captured within the quilted pockets between the fabric layers, increasing the sorbent capacity. Quiltec I has more than twice the adsorbent capacity of a single layer wipe.

Quiltec I has laser-cut, heatsealed edges which reduce the number of releasable particles and fibers. As a knitted polyester product, it is abrasion and chemical resistant and extremely low in particles and fibers.

Sterile Quiltec is validated sterile to a 10⁻⁶ SAL per ANSI/AAMI/ISO 11137 guidelines. A certificate of sterility is provided with each shipment.

These wipes meet the requirements of USP<797> and IEST-CC-RP004.4 for lint-free wipes.



Features	Benefits	
Extremely low in both particles and fibers	Reduces possibility of contamination	
Strong fabric	Abrasion and chemical resistant	
Laser-cut sealed edges	• Reduces particle and fiber generation reducing possibility of contamination	

PDSW058 | 020425

Copyright © 2025 Contec, Inc. All rights reserved.

Contact us: info@contecinc.com contecinc.com Contec, Inc. Spartanburg, SC 29303 USA tel: +1-864-503-8333



Part No.	Description		Size	Packaging
QT1-99	Quiltec I Wipes, Flat stacked		9" x 9" (230 x 230 mm)	50/bag; 20 bags/case
QT1-1212	Quiltec I Wipes, Flat stacked		12" x 12" (305 x 305 mm)	50/bag; 10 bags/case
QT1-44B	Quiltec I Wipes, Flat stacked		4" x 4" (102 x 102 mm)	300/bag; 8 bags/case
QT1-66B	Quiltec I Wipes, Flat stacked		6" x 6" (152 x 152 mm)	200/bag; 10 bags/case
QT1-99B	Quiltec I Wipes, Flat stacked		9" x 9" (230 x 230 mm)	150/bag; 6 bags/case
QT1-1212B/100	Quiltec I Wipes, Flat stacked		12" x 12" (305 x 305 mm)	100/bag; 5 bags/case
LWQS0001	Quiltec I Wipes, Flat stacked	Sterile	9" x 9" (230 x 230 mm)	25/bag; 40 bags/case
LWQS0002	Quiltec I Wipes, Flat stacked	Sterile	12" x 12" (305 x 305 mm)	25/bag; 20 bags/case
LWQT0019	Quiltec I Wipes, Flat stacked		18" x 18" (460 x 460 mm)	25/bag; 8 bags/case
LWQT0031	Quiltec I Wipes, Flat stacked	Sterile	12" x 12" (305 x 305 mm)	10/bag; 50 bags/case
LWQT0034	Quiltec I Wipes, Flat stacked		29.5" x 29.5" (749 x 749 mm)	20/bag; 4 bags/case
LWQT0100	Quiltec I Wipes		10" x 17" (250 x 432 mm)	20/bag; 12 bags/case

Product Information			
Material	• 100% knitted polyester		
Construction	• 2-layer, ultrasonically bonded, interlock knit		
Packaging materials	 Outer bags (OB1, OB2), low density polyethylene (LDPE) Case (CS), corrugated fiberboard (PAP) 		
Environment	• ISO 3-5 Grade A/B for sterile, C/D for nonsterile		
Shelf life	Sterile: 2 years from manufacturing date		

LDPE



Recycle Symbols



PDSW058 | 020425







Copyright © 2025 Contec, Inc. All rights reserved.

Contact us: info@contecinc.com contecinc.com Contec, Inc. Spartanburg, SC 29303 USA tel: +1-864-503-8333



Technical Data						
Attribute (units)	Typical Value	Test Method				
Basis weight, nominal; (g/m²)	240	Contec Method				
Sorbent capacity; (mL/m²)	581	IEST-RP-CC004.3, Sec. 8.1				
Sorptive rate; (seconds)	<1					
Non-volatile residue, NVR		IEST-RP-CC004.3, Sec. 7.1.2				
In deionized water; (g/m²)	0.016					
In isopropyl alcohol; (g/m²)	0.009					
Specific ions		IEST-RP-CC004.3, Sec. 7.2.2				
Sodium; (ppm)	0.050					
Chloride; (ppm)	0.030					
Particles, readily releasable						
Particles $\geq 0.5 \mu m$; (x10 ⁶ /m ²)	5.7	IEST-RP-CC004.2, Sec. 5.1				
Fibers <u>></u> 100µm; (x 10³/m²)	0.140	IEST-RP-CC004.2, Sec. 5.2				

	EA/OB1	OB1/OB2	OB2/CS	EA/CS
LWQS0001	25	4	10	1,000
LWQS0002	25	4	5	500
LWQT0019	25	1	8	200
LWQT0031	10	5	10	500
LWQT0034	20	1	4	80
LWQT0100	20	1	12	240
QT1-44B	300	1	8	2,400
QT1-66B	200	1	10	2,000
QT1-99	50	2	10	1,000
QT1-99B	150	1	6	900
QT1-1212	50	2	5	500
QT1-1212B/100	100	1	5	500

EA = each; OB = outer bag; CS = case

Notes

a) The data shown are typical values and should not be used as product specifications.

b) Valid product comparisons may only be obtained through side-by-side testing in the same test facility, under similar conditions.

c) Current and/or comparison data may be available. Please contact a Contec sales representative for details.

Test Methods:

1. CTM = Contec Test Method

2. IEST-RP-CC004.3 = Evaluating Wiping Materials Used in Cleanroom and Other Controlled Environments, Institute of environmental Sciences and Technology, Rolling Meadows IL

PDSW058 | 092322

Copyright $\ensuremath{\mathbb{C}}$ 2022 Contec, Inc. All rights reserved.

Contact us: info@contecinc.com contecinc.com Contec, Inc. Spartanburg, SC 29303 USA tel: +1-864-503-8333

