## **Twill Jean Wipes**

## 100% woven cotton wipe in a twill construction

The Twill Jean Wipe is a 100% cotton fabric, woven in a  $2 \times 1$  twill construction. The Twill Jean Wipe is very absorbent and has high thermal stability for high temperature applications. The edges are bias cut to prevent unraveling.

Excellent for surface cleaning or spill pick up.



Features	Benefits
Strong and absorbent	Suitable for high temperature applications
Bias cut edges	Reduce unraveling
Sorbent wipe	Suitable for surface cleaning or spill pick up

Part No.	Description	Size	Packaging
TJ-99	Twill Jean Wipes,	9" x 9"	300/bag;
	Flat stacked	(230 x 230 mm)	12 bags/case
TJ-1212	Twill Jean Wipes,	12" x 12"	150/bag;
	Flat stacked	(305 x 305 mm)	10 bags/case
TJ-1717	Twill Jean Wipes,	9" x 9"	75/bag;
	Bulk	(230 x 230 mm)	12 bags/case

PDSW063 | 092722

Copyright © 2022 Contec, Inc. All rights reserved.

Contact us: info@contecinc.com contecinc.com Contec, Inc. Spartanburg, SC 29303 USA tel: +1-864-503-8333



Product Information		
Material	• 100% cotton	
Construction	• Twill	
Packaging materials	<ul> <li>Outer bags (OB1, OB2), low density polyethylene (LDPE)</li> <li>Case (CS), corrugated fiberboard (PAP)</li> </ul>	

Technical Data					
Attribute (units)	Typical Value	Test Method			
Basis weight, nominal; (g/m²)	190	Contec Method			
Sorbent capacity; (mL/m <sup>2</sup> )	300	IEST-RP-CC004.3, Sec. 8.1			
Sorptive rate; (seconds)	1.5	IEST-RP-CC004.3, Sec. 8.2			
Non-volatile residue, NVR		IEST-RP-CC004.3, Sec. 7.1.2			
In deionized water; (g/m²)	0.405				
In isopropyl alcohol; (g/m²)	0.151				
Specific ions		IEST-RP-CC004.3, Sec. 7.2.2			
Sodium; (ppm)	105				
Chloride; (ppm)	10				
Particles, readily releasable					
Particles <u>&gt;</u> 0.5µm; (x10 <sup>6</sup> /m <sup>2</sup> )	80	IEST-RP-CC004.2, Sec. 5.1			
Fibers ≥ 100μm; (x 10³/m²)	98	IEST-RP-CC004.2, Sec. 5.2			

Recycle Symbols				
PET				
HDPE				
LDPE				
PP				
	_			

PAP

Packaging	EA/OB1	OB1/OB2	OB2/CS	EA/CS
TJ-99	300	1	12	3,600
TJ-1212	150	1	10	1,500
TJ-1717	75	1	12	900

EA = each; OB = outer bag; CS = case

## Notes

a) The data shown are typical values and should not be used as product specifications.

b) Valid product comparisons may only be obtained through side-by-side testing in the same test facility, under similar conditions. c) Current and/or comparison data may be available. Please contact a Contec sales representative for details.

Test Methods:

1. CTM = Contec Test Method

2. IEST-RP-CC004.3 = Evaluating Wiping Materials Used in Cleanroom and Other Controlled Environments, Institute of environmental Sciences and Technology, Rolling Meadows IL

PDSW063 | 092722

Copyright © 2022 Contec, Inc. All rights reserved.

Contact us: info@contecinc.com contecinc.com Contec, Inc. Spartanburg, SC 29303 USA tel: +1-864-503-8333

